

Synthetic Turf Rugby League Pre-match Maintenance Checks										
Club Name / pitch location		Stobbart Stadium, Widness RFLC								
Date and time of game										
Date and time of pitch inspection										
Measurements made by		Name								
		Position								
Measured infill depth (mm)										
Manufacturer's declaration					40mm					
Minimum		90% of manufacturer's specification			<36mm					
Maximum		110% of manufacturer's specification			> 44mm					
Grid position										
	A	B	C	D	E	F	G	H	I	
-5										
0										
10										
20										
30										
40										
50										
60										
70										
80										
90										
100										
105										

Note ideally vertical free pile heights will be within +/- 2mm of the manufacturer's specification. If values are found outside this range additional maintenance is advised.

Measured vertical free pile height (mm)										
Manufacturer's declaration					20mm					
Minimum		75% of manufacturer's specification			15mm					
Maximum		125% of manufacturer's specification			25mm					
Grid position										
	A	B	C	D	E	F	G	H	I	
-5										
0										
10										
20										
30										
40										
50										
60										
70										
80										
90										
100										
105										

Note ideally vertical free pile heights will be within +/- 2mm of the manufacturer's specification. If values are found outside this range additional maintenance is advised.

**Statement of compliance**

The data recorded above is a true record of the condition of the synthetic turf pitch at the time of test.

	Tick appropriate box
Infill depths were found to be within tolerance in all positions	<input type="checkbox"/>
Infill depths were found to be out of tolerance in certain positions *	<input type="checkbox"/>
Vertical free pile heights were found to be within tolerance in all positions	<input type="checkbox"/>
Vertical free pile heights were found to be out of tolerance in certain positions *	<input type="checkbox"/>
Signed	

If the vertical free pile height or infill depth is found to be out of tolerance in any test position appropriate remedial works shall be undertaken to rectify the defect and a further set of measurements made to verify compliance with RFL competition regulations.

Copies of this completed form shall be retained by the Club. Copies shall be submitted to the RFL or their Match Officials as requested.

Review of inspection data and appropriate actions to ensure the playing surface complies with the surface manufacturer's recommendations and RFL competition regulations at all times remains the sole responsibility of the Club.

**Test positions (mark identifying location on plan to enable positions to be identified for future reference)**

Test positions	A	B	C	D	E	F	G	H	I	
	Run-off	10m	20m	30m	40m	50m	60m	68m	Run-off	
-5	Dead ball zone									
0	Try line									
10	10m									
20	20m									
30	30m									
40	40m									
50	50m									
60	40m									
70	30m									
80	20m									
90	10m									
100	Try line									
105	Dead ball zone									